

Discriminator II

The only coin returning system with 2-coin intelligent payment to make payments which optimise space and change combinations.

2 COINS
6 COINS





Amusement



Transport
& Parking



Retail
& Banking



Kiosk

Discriminator II

INTELLIGENT DESIGN

- An only design, 6 different capacities of storage
- Reliability and exactitude in the counted one of currencies
- Anti-jamming and anti-span design
- Flash Technology
- Simplified programming
- Payment multicurrency: it distinguishes 2-6 currencies in an only Hopper
- Simplified calibration
- Intelligent payment: it diminishes incidences by lack of change

Mechanical Characteristics

Coin diameters	18 mm - 30 mm
Coin thickness	1.7 mm - 3.2 mm
Dimensions	115 x 131 x 155 mm
Degrees of inclination	3° on all axes
Payment Speed	up 5,4 coin/sec.
Coin Capacity	up 750 coin (1€)

Electrical Characteristics

Voltage	Nominal	12-24 V
	Minimum	10,8 Vdc
	Maximum	36,4 Vdc
Current	Standard	450 mA
	Maximum	3 A

Working Conditions

Working Temperature	+5°C to +55°C
Relative Humidity (without condensation)	95 %
Storage Temperature	-25°C to +70°C

Accessories

- Three hopper sizes
- Full overflow
- Empty and full sensors

Protocols

Parallel

ccTalk

Discriminator II

-

